

# SAFETY DATA SHEET



Revision Date: 01/21/2016

## 1. IDENTIFICATION

**Product Name:** Anionic Emulsified Asphalt

**Synonym:** Anionic Emulsified Asphalt; HFMS-2; HFRS-1; HFRS-2; MS-2; RS-1; RS-2; RS-2L; RS-2P; SS-1; SS-1H; SS-1HL; HFMS-2H

**Chemical Family:** Asphalt

**Recommended Use:** Road Building & Other Service.

**Use Restrictions:** All others.

**Supplier Name and Address:**  
**Peckham Industries, Inc.**  
**20 Haarlem Ave.**  
**White Plains, NY 10603**

**SDS information:** 1-914-949-2000

**Emergency Telephone: Chemtrec** 1-800-424-9200

## 2. HAZARD IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1A
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

### Hazards Not Otherwise Classified (HNOC)

Hot liquid may cause thermal burns  
May release hydrogen sulfide gas

### Label elements

## EMERGENCY OVERVIEW

### Warning

Contact with product at elevated temperatures can result in thermal burns  
May release highly toxic hydrogen sulfide gas that quickly fatigues the sense of smell  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
May cause damage to organs (liver, spleen, bone marrow) through prolonged or repeated exposure  
Toxic to aquatic life with long lasting effects  
Up to 10% of the mixture consists of ingredient(s) of unknown toxicity



**Appearance** Black-brown solid or semi-solid at room temperature. Liquid at temperatures >70°C.

**Physical State** Liquid

**Odor** Hydrocarbon / Tar

### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Wash hands and any possibly exposed skin thoroughly after handling  
Contaminated work clothing should not be allowed out of the workplace  
Avoid release to the environment

### Precautionary Statements – Response

**IF** exposed or concerned: Get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical attention. **IF ON SKIN:** Wash with plenty of soap and water If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a **POISON CENTER** or doctor if you feel unwell. Collect spillage.

### Precautionary Statements - Storage

Store locked up

### Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is an Anionic Emulsified Asphalt mixed with varying proportions of No. 2 fuel oil and an anionic emulsifier. May contain polymer modifiers. Composition varies depending on source of crude and specifications of final product. May contain minor amounts of sulfur, nitrogen and oxygen containing compounds.

### Composition Information:

Name Weight %	CAS	Number
Asphalt	8052-42-4	30-75
Distillates (petroleum), straight-run middle	64741-44-2	0-40
Sulfur Compounds	Mixture	0.5-5.0
Polymer Modifier (SBS or SBR)	Mixture	0-5
Anionic Emulsifier	Mixture	0.1-4
Polyamine	Proprietary	0-1
Naphthalene 0.2	91-20-3	0.01-
Polycyclic Aromatic Hydrocarbons	Mixture	<0.1
Hydrogen sulfide	7783-06-4	0-0.1

## 4. FIRST AID MEASURES

### First Aid Measures

**General advice** Immediately address any airway, breathing, or circulation concerns. Contact EMS if the person is having trouble breathing, moving, or staying awake. Perform a quick assessment for other injuries that may be present including falls or from falling objects. **REMEMBER ABCC (AIRWAY, BREATHING, CIRCULATION, COOLING).**

**Inhalation:** If symptoms of overexposure to asphalt fume develop, move to fresh air in a position comfortable for breathing. If symptoms or irritation occur, call a poison control center or doctor.

**Skin Contact:** Hot material: **DO NOT DELAY.** Immediately immerse or place the affected skin under a water stream for at least 20 minutes. Urgent medical attention is required for burns to the face, eyes, hands, feet, genitalia, and for circumferential or large burn areas. **GET MEDICAL ATTENTION IMMEDIATELY.** Do not attempt to remove solidified asphalt if not a physician. Leave burn uncovered. Ice (or "cold packs") may be used in the event that water is unavailable. Only remove clothing if not adhering to the skin. Be aware that although it is very important to cool the burn thoroughly and completely, the overuse of ice may increase the risk of hypothermia. Cold material: To remove cold asphalt not associated with a burn, wash with soap and water or waterless cleaner. If symptoms or irritation or rash occur, call a poison control center or doctor.

**Eye Contact:** Hot material: After contact with hot asphalt, lay the person flat on their back, remove contact lenses if easy to do, and flush with water from a continuous stream for at least 20 minutes by allowing the water to flow over the bridge of the nose to the eyes. **GET MEDICAL ATTENTION IMMEDIATELY.** Cold material: If irritation develops, flush eyes with water. If irritation or redness persists call a poison control center or a doctor.

**Ingestion:** Ingestion not likely. Small amounts of ingested asphalt usually require no treatment. If large amounts are swallowed, call a poison control center or doctor.

### **Most important signs and symptoms, both short-term and delayed with overexposure**

#### **Adverse Effects:**

Frequent or prolonged contact with cold material may cause irritation. Additional effects may include skin sensitization. Exposure to hot melted material can cause thermal burns.

### **Indication of any immediate medical attention and special treatment needed**

**NOTES TO PHYSICIAN:** Immediately address any airway, breathing, or circulation concerns.

**SKIN & EYE CONTACT:** Prolonged flushing/cooling is necessary if the patient is treated on scene or soon after asphalt contact. Topical antibiotics should be liberally applied to the adhered asphalt-skin interface to aid in asphalt removal. A non-adherent material, such as Adaptic®, can then be applied and covered with sterile gauze. If topical antibiotics are not available, other materials that may be effective include mineral oil, baby oil, petroleum jelly (e.g. Vaseline®), mayonnaise, or butter. Do not use organic solvents such as kerosene, gasoline, or ethanol, as these can result in tissue damage or a fire hazard. Dressings should be changed every 4 hours until natural separation occurs. Initiate standard burn management at that time. Once cooled, adhered asphalt is not harmful to the skin, and in fact, provides a sterile cover over the affected area. The asphalt will detach itself within a few days as healing occurs. If it is necessary to remove the asphalt, only medically approved solvents or warm paraffin should be used to prevent further skin damage. Circumferential asphalt contact can have a tourniquet effect and impair distal circulation and nerve function. Create a longitudinal split or cut (analogous to an escharotomy) may be required completely across the residual asphalt to relieve pressure in the underlying tissue. For eye exposures with adherent asphalt, consult with an ophthalmologist. If hot material has caused burns to the eye, early ophthalmologic evaluation is recommended.

**INHALATION:** Inhalation exposure can produce toxic effects. Treat intoxications as hydrogen sulfide exposures. At high concentrations hydrogen sulfide may produce pulmonary edema, respiratory depression, and/or respiratory paralysis. The first priority in treatment should be the establishment of adequate ventilation and the administration of 100% oxygen. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO<sub>2</sub>, dry chemical, foam (AFFF/ATC) or water fog can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

### Unsuitable extinguishing media

Do not use straight streams. Water contact can cause violent eruption of hot asphalt.

### Specific hazards arising from the chemical

This product is not a combustible liquid per the OSHA Hazard Communication Standard, but will ignite and burn at temperatures exceeding the flash point. For additional fire related information, see NFPA 30 or the Emergency Response Guidebook 128.

### Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

### Explosion data

**Sensitivity to Mechanical Impact** No.  
**Sensitivity to Static Discharge** No.

### Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full face-piece, as appropriate. Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Keep run-off water out of sewers and water sources.

**NFPA:** Health 2 Flammability 1 Instability 0 Special Hazards -

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Keep public away. Isolate and evacuate area. Shut off source if safe to do so.

**Protective Equipment:** Use personal protection measures as recommended in Section 8.  
**Emergency Procedures:** Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.

**Environmental precautions:** Avoid release to the environment. Avoid subsoil penetration.  
**Methods and materials for containment:** Contain liquid with sand or soil.

**Methods and materials for cleaning up:** Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers.

## 7. HANDLING AND STORAGE

**Safe Handling Precautions:** Avoid contact with skin, eyes and clothing. Avoid breathing fumes, gas, or vapors. Use only with adequate ventilation. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements.

Harmful concentrations of hydrogen sulfide (H<sub>2</sub>S) gas can accumulate in excavations and low-lying areas as well as the vapor space of storage and bulk transport compartments. Stay upwind and vent open hatches before unloading. Sulfur containing

products may cause polysulfide deposits (iron sulfide) to form inside iron storage tanks. These pyrophoric deposits, upon exposure to air, can ignite spontaneously. Keep heating coils and flues in storage tanks, trucks and kettles covered with product (8"). Do not overheat.

**Storage Conditions:** Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area.  
**Incompatible materials** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELs:	OSHA - Vacated PELs	NIOSH IDLH
Asphalt 8052-42-4	0.5 mg/m <sup>3</sup> TWA	-	-	-
Distillates (petroleum), straight-run middle 64741-44-2	-	-	-	-
Sulfur Compounds), Mixture	-	-	-	-
Polymer Modifier (SBS or SBR) Mixture	-	-	-	-
Anionic Emulsifier Mixture	-	-	-	-
Polyamine Proprietary	-	-	-	-
Naphthalene 91-20-3	10 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup>	10 ppm TWA 50 mg/m <sup>3</sup> TWA 15 ppm STEL 75 mg/m <sup>3</sup> STEL	250 ppm
Polycyclic Aromatic Hydrocarbons Mixture	-	-	-	-
Hydrogen sulfide 7783-06-4	1 ppm TWA 5 ppm STEL	Ceiling: 20 ppm	10 ppm TWA 14 mg/m <sup>3</sup> TWA 15 ppm STEL 21 mg/m <sup>3</sup> STEL	100 ppm

**Notes:** The manufacturer has voluntarily elected to provide exposure limits contained in OSHA's 1989 air contaminants standard in its SDSs, even though certain of those exposure limits were vacated in 1992.

**Engineering measures:** Local or general exhaust required in an enclosed area or when there is inadequate ventilation.

### Personal protective equipment

**Eye protection:** Wear goggles and faceshield when handling hot material.

**Skin and body protection:** Wear insulated gloves when handling hot material. Contact the glove manufacturer for specific advice on glove selection and breakthrough times. Rubberized suits or coats may be needed for some maintenance operations with hot material.

**Respiratory protection:** Where there is potential for airborne exposure to hydrogen sulfide (H<sub>2</sub>S) above exposure limits, a NIOSH approved, self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode should be used. When H<sub>2</sub>S vapors exceed permissible limits, i.e., in confined spaces or bulk transport loading/unloading, a positive-pressure atmosphere supplying respirator is recommended. Self-contained breathing apparatus should be used for fire fighting.

Provided hydrogen sulfide (H<sub>2</sub>S) is not detected: if there is potential to exceed the exposure limits for asphalt fumes a NIOSH certified air purifying respirator equipped with organic vapor cartridges/canisters with R or P95 filters should be used. A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed when conditions warrant the use of a respirator.

Note: Air purifying respirators are not to be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient atmospheres, (less than 19.5 percent oxygen) or under conditions that are immediately dangerous to life and health (IDLH).

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Black-brown solid or semi-solid at room temperature. Liquid at temperatures >70°C.
<b>Color</b>	Dark brown to black
<b>Odor</b>	Hydrocarbon / Tar
<b>Odor Threshold</b>	No available data.

Property	Values (Method)
<b>Melting Point / Freezing Point</b>	No available data.
<b>Initial Boiling Point / Boiling Range</b>	> 100 °C / > 212 °F (ASTM D6997)
<b>Flash Point</b>	No available data.
<b>Evaporation Rate</b>	No available data.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammability Limit in Air (%)</b>	
<b>Upper Flammability Limit:</b>	No available data.
<b>Lower Flammability Limit:</b>	No available data.
<b>Vapor Pressure</b>	Negligible @ 25°C (ASTM D323)
<b>SDS ID NO.:</b>	0137MAR019
<b>Vapor Density</b>	
<b>Specific Gravity / Relative Density</b>	0.95-1.05 @ 15.6°C (ASTM D70)
<b>Water Solubility</b>	Negligible
<b>Solubility in other solvents</b>	No available data.
<b>Partition Coefficient</b>	No available data.
<b>Decomposition temperature:</b>	No available data.
<b>pH:</b>	Not applicable.
<b>Autoignition Temperature</b>	No available data.
<b>Kinematic Viscosity</b>	No available data.
<b>Dynamic Viscosity</b>	No available data.
<b>Explosive Properties</b>	No available data.
<b>Softening Point</b>	No available data.
<b>VOC Content (%)</b>	No available data.
<b>Density</b>	No available data.
<b>Bulk Density</b>	Not applicable.

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	The product is non-reactive under normal conditions.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	Will not occur.
<b>Conditions to avoid</b>	Sources of heat or ignition.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	None known under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Potential short-term adverse effects from overexposures

**Inhalation** Harmful if inhaled. Fumes or vapors from the heated material may be irritating to the respiratory tract. May cause drowsiness or dizziness. May release highly toxic hydrogen sulfide gas that quickly fatigues the sense of smell.

**Eye contact** Vapors may cause eye irritation and sensitivity to light. Contact with hot material may cause thermal burns.

**Skin contact** May cause skin irritation. May cause an allergic skin reaction. Contact with hot material may cause thermal burns.

**Ingestion** If swallowed at ambient temperature no significant adverse effects are expected. Ingestion of large amounts may cause gastrointestinal blockage. Swallowing hot material may cause burns to the mouth, throat, and stomach.

**Acute Toxicological data**

Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>94.4 mg/m <sup>3</sup> (Rat) 4 h
Distillates (petroleum), straight-run middle 64741-44-2	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	1700 mg/m <sup>3</sup> (Rat) 4 h
Sulfur Compounds Mixture	-	-	> 5 mg/l (Rat) 4 h
Polymer Modifier (SBS or SBR) Mixture	-	-	-
Anionic Emulsifier Mixture	-	-	-
Polyamine Proprietary	-	-	-
Naphthalene 91-20-3	490 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 340 mg/m <sup>3</sup> (Rat) 1 h
Polycyclic Aromatic Hydrocarbons Mixture	-	-	-
Hydrogen sulfide 7783-06-4	-	-	444 ppm (Rat) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**PETROLEUM ASPHALT:** Eye and upper respiratory tract irritation has been reported in some asphalt workers (paving and roofing operations) but they are typically mild and transient. Some studies indicate that asphalt paving workers may experience lower respiratory tract symptoms (e.g., coughing, wheezing, and shortness of breath) and pulmonary function changes. Other studies of asphalt workers found no consistent relationship between exposure to asphalt fumes and pulmonary function. Increased levels of 1-hydroxypyrene (a marker for exposure to polycyclic aromatic hydrocarbons) have been observed in the urine of asphalt workers. Genotoxicity studies (e.g., DNA adducts in the urine) of asphalt workers have been largely inconclusive. A slight increase in lung cancer mortality was reported in a study of European workers exposed to paving and mastic asphalt, but conclusions were equivocal. A follow-up case-control epidemiology study of asphalt paving workers sponsored by the International Association for Research in Cancer (IARC) concluded that there was no evidence that asphalt exposure was linked to lung cancer. An increase in skin tumors was observed in lifetime studies of laboratory rodents exposed to extracts of asphalt (bitumen). The relevance of these studies to humans is not clear. No increase in skin tumors was observed in a lifetime bioassay where laboratory mice were treated with paving fume condensates. No increase in lung or other tumors were observed in a lifetime inhalation study in laboratory rats exposed to fumes from paving asphalt.

**ASPHALTS USED IN ROOFING OPERATIONS:** Some asphalts including roofing flux are further processed (oxidized/air-rectified) by the user or customer before use. An increased incidence of skin tumors was observed in a mouse skin carcinogenicity study where animals were exposed to condensed fumes collected from an oxidized roofing asphalt (BURA Type III) at above 450°F. Additional studies where mice were exposed to oxidized roofing asphalt fume condensates both as a tumor initiator and as a tumor promoter indicate that roofing fume condensate caused tumors as a result of initiation.

**MIDDLE DISTILLATES, PETROLEUM:** Long-term repeated (lifetime) skin exposure to similar materials has been reported to result in an increase in skin tumors in laboratory rodents. The relevance of these findings to humans is not clear at this time.

**NAPHTHALENE:** Severe jaundice, neurotoxicity (kernicterus) and fatalities have been reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays have been negative. A few studies have shown chromosomal effects

(elevated levels of Sister Chromatid Exchange or chromosomal aberrations) in vitro. Naphthalene has been classified as Possibly Carcinogenic to Humans (2B) by IARC, based on findings from studies in laboratory animals.

**HYDROGEN SULFIDE:** Hydrogen sulfide gas has an unpleasant odor that diminishes with increased exposure. Eye irritation may occur at levels above 4 ppm. Olfactory fatigue occurs rapidly at levels of 50 ppm or higher. Odor is not a reliable warning property. Respiratory effects include irritation with possible pulmonary edema at levels above 50 ppm. At 500 ppm immediate loss of consciousness and death can occur. NIOSH has determined that 100 ppm hydrogen sulfide is immediately dangerous to life and health (IDLH).

**POLYCYCLIC AROMATIC HYDROCARBONS (PAHs):** Cancer is the most significant endpoint for PAHs. Certain PAHs are weak carcinogens which become carcinogenic after undergoing metabolism. Chronic or repeated exposure increases the likelihood of tumor initiation. Increased incidence of tumors of the skin, bladder, lung and gastrointestinal tract have been described in individuals overexposed to certain PAHs. Overexposure to PAHs has also been associated with photosensitivity and eye irritation. Inhalation overexposure of PAHs has been associated with respiratory tract irritation, cough, and bronchitis. Dermal overexposure has been associated with precancerous lesions, erythema, dermal burns, photosensitivity, acneiform lesions and irritation. Oral overexposure to PAHs has been associated with precancerous growths of the mouth (leukoplakia). Mild nephrotoxicity, congestion and renal cortical hemorrhages and elevated liver function tests, changes in the immune system and other effects have been observed in rats exposed to high levels of PAHs by ingestion. The International Agency for Research on Cancer (IARC) has concluded that some PAHs are probably carcinogenic to humans.

**Adverse effects related to the physical, chemical and toxicological characteristics**

**Signs & Symptoms** Frequent or prolonged contact with cold material may cause irritation. Rash. Contact with hot material may cause thermal burns.

**Sensitization** May cause sensitization by skin contact. Not expected to be a respiratory sensitizer.

**Mutagenic effects** None known.

**Carcinogenicity** Cancer designations are listed in the table below.

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Asphalt 8052-42-4	Not classifiable (A4)	Emissions of straight-run asphalt from paving operations - Possible human carcinogen (2B)	Not Listed	Not Listed
Distillates (petroleum), straight-run middle 64741-44-2	Not Listed	Not Listed	Not Listed	Not Listed
Sulfur Compounds Mixture	Not Listed	Not Listed	Not Listed	Not Listed
Polymer Modifier (SBS or SBR) Mixture	Not Listed	Not Listed	Not Listed	Not Listed
Anionic Emulsifier Mixture	Not Listed	Not Listed	Not Listed	Not Listed
Polyamine Proprietary	Not Listed	Not Listed	Not Listed	Not Listed
Naphthalene 91-20-3	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not Listed
Polycyclic Aromatic Hydrocarbons Mixture	Suspected human carcinogen (A2)	Carcinogenic to humans (1) be a human carcinogen	Reasonably anticipated to	Not Listed
Hydrogen sulfide 7783-06-4	Not Listed	Not Listed	Not Listed	Not Listed

**Reproductive toxicity** None known.

**Specific Target Organ Toxicity (STOT) - single exposure** Not classified.

**Specific Target Organ Toxicity** Not classified. Liver. Spleen. Bone marrow.



**(STOT) - repeated exposure**

**Aspiration hazard** Potential for aspiration if swallowed.

**Unknown Acute Toxicity** Up to 10% of the mixture consists of ingredient(s) of unknown toxicity

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** This product should be considered toxic to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment.

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Asphalt 8052-42-4	-	-	-	-
Distillates (petroleum), Shrimp straight-run middle 64741-44-2	-	-	-	48-hr TLM = 4.1 ppm
Sulfur Compounds Mixture	-	-	-	-
Polymer Modifier (SBS or SBR) Mixture	-	-	-	-
Anionic Emulsifier Mixture	-	-	-	-
Polyamine Proprietary	-	-	-	-
Naphthalene 91-20-3	-	96-hr LC50 = 0.91-2.82 mg/l Rainbow trout (static) 96-hr LC50 = 1.99 mg/l Fathead minnow (static)	-	48-hr LC50 = 1.6 mg/l Daphnia magna
Polycyclic Aromatic Hydrocarbons Mixture	-	-	-	-
Hydrogen sulfide 7783-06-4	-	96-hr LC50 = 0.016 mg/l Fathead minnow 96-hr LC50 = 0.013 mg/l Rainbow trout	-	-

**Persistence and degradability** Not expected to be readily biodegradable.  
**Bioaccumulation** Not expected to bioaccumulate in aquatic organisms.  
**Mobility in soil** Not likely to move rapidly with surface or groundwater flows because of its low water solubility.  
**Other adverse effects** No information available.

## 13. DISPOSAL CONSIDERATIONS

### Description of Waste Residues

No information available.

### Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required.

### Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

### Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Dispose of in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

**DOT (49 CFR 172.101):**  
**UN Proper shipping name:** Not Regulated  
**UN/Identification No:** Not applicable  
**Transport Hazard Class(es):** Not applicable  
**Packing group:** Not applicable

**TDG (Canada):**  
**UN Proper shipping name:** Not Regulated  
**UN/Identification No:** Not applicable  
**Transport Hazard Class(es):** Not applicable  
**Packing group:** Not applicable

## 15. REGULATORY INFORMATION

**US Federal Regulatory Information:**

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA Chemical Inventory.

**EPA Superfund Amendment & Reauthorization Act (SARA):**

**SARA Section 302:** This product may contain component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Asphalt	NA
Distillates (petroleum), straight-run middle	NA
Sulfur Compounds	NA
Polymer Modifier (SBS or SBR)	NA
Anionic Emulsifier	NA
Polyamine	NA
Naphthalene	NA
Polycyclic Aromatic Hydrocarbons	NA
Hydrogen sulfide	500 lb TPQ

**SARA Section 304:** This product may contain component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Asphalt	NA
Distillates (petroleum), straight-run middle	NA
Sulfur Compounds	NA
Polymer Modifier (SBS or SBR)	NA
Anionic Emulsifier	NA
Polyamine	NA
Naphthalene	100 lb final RQ 45.4 kg final RQ
Polycyclic Aromatic Hydrocarbons	1 lb final RQ 0.454 kg final RQ
Hydrogen sulfide	100 lb final RQ 45.4 kg final RQ

**SARA:** The following EPA hazard categories apply to this product:

- Acute Health Hazard
- Chronic Health Hazard

**SARA Section 313:**

This product may contain component(s), which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Asphalt	None
Distillates (petroleum), straight-run middle	None
Sulfur Compounds	None
Polymer Modifier (SBS or SBR)	None
Anionic Emulsifier	None
Polyamine	None
Naphthalene	0.1 % de minimis concentration
Polycyclic Aromatic Hydrocarbons	0.1 % Supplier notification limit
Hydrogen sulfide	1.0 % de minimis concentration

## 16. OTHER INFORMATION

**Prepared By** Toxicology and Product Safety  
**Revision Date:** 01/21/2016  
**Revision Note:**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.